



CAPACITORS FOR AC AND DC GENERAL PURPOSE APPLICATIONS

TARGETED APPLICATIONS

- Filtering
- Power Supply
- Power Conversion

SPECIFICATIONS

- Voltage Range (VAC): 240 to 660
- Capacitance Range (μF): 2 to 120
- Operating Temperature ($^{\circ}\text{C}$): -40 to +70
- Load Life (Hours): 60,000
- Terminal: "Combo" terminal: 1, 2, 3, or 4 tab terminals
- Case Diameters (in.):
1.25, 1.50, 1.75, & 2.00 Oval
1.75, 2.00, & 2.50 Round
- Case Heights (in.): 2.12 to 5.75
- RoHS Compliant
- cULus approved
- CSA certified
- Conforms to EIA-456-A Industry Reliability Standard (meeting 60,000 hours of life)

FEATURES

- Wide range of capacitance and voltage ratings.
- Patented Pressure Sensitive Interrupter (PSI).
- High-Grade Metallized Polypropylene film.
- Subjected to 100% Electrical Testing for:
Capacitance
Dissipation Factor
High-potential electrical withstand

BENEFITS

- Design Flexibility / Product Customization.
- Patented Pressure Sensitive Interrupter (PSI).
- Proven technology with over 60 years of manufacturing experience.

REFERENCES

- www.capcom.mx
- Capacitors for AC and DC General Purpose Applications -Catalogue